Product data sheet Characteristics

SRT48RMBP

APC Smart-UPS SRT 48V 1kVA 1.5kVA RM **Battery Pack**





$\overline{}$						
()	W	Ω	r۱	/16	21	٨/

Lead time Usu	ually in Stock

General

Provided equipment	Documentation CD Installation guide
	Rack mounting brackets Warranty card

Physical

Overview		
Lead time	Usually in Stock	
General		
Provided equipment	Documentation CD	
	Installation guide	
	Rack mounting brackets Warranty card	
	Transity data	
DI : I		
Physical	DI I	
Colour	Black	
Depth	53.6 cm	
Height	8.5 cm	
Net weight	29.9 kg	
Number of rack unit	2U	
Width	43.2 cm	
Environmental		
Ambient air temperature for operation	040 °C	
Operating altitude	010000 ft	
Relative humidity	095 % non-condensing	
Ambient air temperature for storage	-1545 °C	
Storage altitude	0.0015240.00 m	
Batteries & Runtime		
Number of battery free slots	0	
Number of battery filled slots	0	
Device mounting	Stand alone battery stack	

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	010000 ft
Relative humidity	095 % non-condensing
Ambient air temperature for storage	-1545 °C
Storage altitude	0.0015240.00 m

Batteries & Runtime

		7
Number of battery free slots	0	
Number of battery filled slots	0	<u>:</u> ن
Device mounting	Stand alone battery stack	

Battery voltage	48 V
Battery type	Lead-acid battery
Number of battery replacement quantity	2

Packing Units

Package 1 Weight	37 kg	
Package 1 Height	24.4 cm	
Package 1 width	59.4 cm	
Package 1 Length	74.9 cm	
Number of Units in Package 3	6	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration

Contractual warranty

Warranty	2 years repair or replace