

Technical Specifications

APC Easy UPS SRV RM 6000VA 230V with External Battery Pack,with RailKit | SRV6KRILRK | Downloaded on 09/03/2019 (EST)



APC Easy UPS SRV RM 6000VA 230V with External Battery Pack,with RailKit

SRV6KRILRK

Call for More Information *6798 / +972 9 830 55 29

- High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions
- Includes: CD with software, USB cable, User Manual

Output

Output power capacity	6.0kWatts / 6.0kVA
Max Configurable Power (Watts)	6.0kWatts / 6.0kVA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Waveform type	Sine wave

Input

Nominal Input Voltage	230V
Input frequency	40 - 70 Hz
Input Connections	Hard Wire 3-wire
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Extendable Run Time	1
Battery Volt-Amp-Hour Capacity	1512
Extended Run Options	APC-Easy-UPS-SRV-RM-6000VA-230V-with-External-Battery-Pack-with-RailKit (Available in Technical Tab on site)
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)

Communications & Management

Control panel	Multi-function LCD status and control console
---------------	---

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
---------------	--

Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

Physical

Maximum Height	173MM, 17.3CM
----------------	---------------

Maximum Width	438MM, 43.8CM
---------------	---------------

Maximum Depth	710MM, 71.0CM
---------------	---------------

Net Weight	61.0KG
------------	--------

Shipping weight	71.0KG
-----------------	--------

Environmental

Operating Temperature	0 - 40 °C
-----------------------	-----------

Operating Relative Humidity	0 - 95 %
-----------------------------	----------

Operating Elevation	0-3000meters
---------------------	--------------

Storage Relative Humidity	0 - 95 %
---------------------------	----------

Storage Elevation	0-14763.6meters
-------------------	-----------------

Sustainable Offer Status

RoHS	Compliant
------	-----------

REACH	REACH: Contains SVHCs
-------	-----------------------

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.