



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Installation guide Warranty card
--------------------	-------------------------------------

Physical

Colour	Black
Depth	68.27 cm
Height	13 cm
Net weight	91 kg
Number of rack unit	3U
Width	43.2 cm

Conformance

Standards	OSHDP
-----------	-------

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Storage Relative Humidity	Non-condensing 0...95 %

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	192 V
Battery type	Lead-acid battery
Number of battery replacement quantity	2

Packing Units

Package 1 Weight	105.5 kg
Package 1 Height	42 cm
Package 1 width	60 cm
Package 1 Length	100 cm
Number of Units in Package 3	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------