



Price\* : 1,159.20 USD



## Overview

Lead time Usually in Stock

## General

Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet USB cable Warranty card
Product web sub-family	High density
Number of tare power	26 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	S

## Physical

Cable length	1.83 m
Colour	Black
Depth	50.5 cm
Height	43.2 cm
Mounting position	Vertical
Mounting preference	No preference
Net weight	20.5 kg
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

\* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Apr 20, 2021

Width	8.5 cm
-------	--------

## Input

Network frequency	40...70 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	100...275 V
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

## Output

Rated power in W	1500 W
Maximum configurable power in W	1500 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13
Bypass type	Built-in bypass
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1500 VA
Rated power in VA	1500 VA

## Conformance

Product certifications	CE EAC
------------------------	-----------

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
Show note OP temperature	No
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Liquid value	0
Battery voltage	48 V
Battery curve	D

Battery charger power	108 W rated
Battery power in VAH	324 VAh runtime
Battery life	3...5 year(s)
Battery option	SRT48BP 1 972 VAh SRT48BP 2 1620 VAh SRT48BP 3 2268 VAh SRT48BP 4 2916 VAh SRT48BP 5 3564 VAh SRT48BP 6 4212 VAh SRT48BP 8 5508 VAh SRT48BP 10 6804 VAh
Extended runtime	1

### Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

### Surge Protection and Filtering

Surge energy rate	432 J
-------------------	-------

### Packing Units

Package 1 Weight	29.6 kg
Package 1 Height	24.6 cm
Package 1 width	59.4 cm
Package 1 Length	74.9 cm
Number of Units in Package 3	12

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
Optimized Energy Efficiency	Energy efficient product

### Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---