



Price* : 1,456.00 USD



Overview

Lead time Usually Ships within 2 Weeks

General

Provided equipment	CD with software Documentation CD USB cable
Product web sub-family	Entry level
Performance multiplier	1
Number of tare power	38 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	5

Physical

Number of rack unit	0U
Colour	Black
Depth	54.4 cm
Height	43.5 cm
Mounting location	Front
Mounting preference	No preference
Net weight	43 kg
Mounting mode	Not rack-mountable

* Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Apr 8, 2021

Two post mountable	0
USB compatible	Yes
Width	19.7 cm

Input

Network frequency	47...63 Hz
Plug standard	IEC 320 C20
Input voltage limits	170...300 V adjustable 180...287 V
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	2100 W
Maximum configurable power in W	2100 W
Harmonic distortion	Less than 5 % at full load
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 1 IEC 320 C19
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Rated power in VA	3000 VA

Conformance

Product certifications	C-Tick CE EAC GOST SABS VDE
------------------------	--

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	45 dBA
Heat dissipation	135 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0

Battery curve	C
Battery charger power	183 W rated
Battery power in VAH	552 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

Communications & Management

Free slots	0
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	300 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	51 kg
Package 1 Height	76.2 cm
Package 1 width	38.1 cm
Package 1 Length	69.9 cm
Number of Units in Package 3	24

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------