

SRV1KIL

APC Easy UPS On-Line SRV Ext. Runtime 1000VA 230V with External Battery Pack



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord 1 x DC cable User manual USB cable
Number of tare power	28 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	1.50 M
Colour	Black
Depth	40 Cm
Height	23.8 Cm
Net weight	24 Kg
USB compatible	No
Width	29 Cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V adjustable (half load) 160...280 V
Inputvolt_other	220 V 240 V
Number of cables	1
Input voltage	230 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Output

Rated power in W	800 W
Maximum configurable power in W	800 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 IEC 60320 C13
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0.0608
Curve load maximum	100 %
Curve load minimum	7 %
Curve proportional loss	0.0545
Curve square loss	0.0077
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	88 % (full load)
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	1000 VA
Rated power in VA	1000 VA
Runtime at 200W	00:24:00
Runtime at 400W	00:11:00

Conformance

Product certifications	CE EAC
Standards	IEC 62040-1-1 IEC 62040-1-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0...15000 M
Acoustic level	50 dB
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 H
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	D
Battery power in VAH	516 VAh runtime
Battery option	SRV36BP-9A 1 1032 VAh SRV36BP-9A 2 1548 VAh SRV36BP-9A 3 2064 VAh SRV36BP-9A 4 2580 VAh SRV36BP-9A

Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous-tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	26.7 Kg
Package 1 Height	35.5 Cm
Package 1 width	47 Cm
Package 1 Length	52.5 Cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **Commercialised**