

# Product datasheet

Specifications



## APC Easy UPS On-Line SRV 3000VA 230V

SRV3KI

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock


### Main

<b>Main Input Voltage</b>	230 V
<b>Product or component type</b>	Uninterruptible power supply (UPS)
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	2400 W
<b>Rated power in VA</b>	3000 VA
<b>Input Connection Type</b>	IEC 60320 C20
<b>output connection type</b>	6 IEC 60320 C13 1 IEC 60320 C19
<b>Cable length</b>	1.5 m
<b>Number of cables</b>	1
<b>Provided equipment</b>	1 IEC 60320 C19 to Schuko power cable 1 IEC 60320 C13 to C14 power cable 1 USB cable 1 RS-232 configuration cable user manual
<b>Range of product</b>	Easy UPS On-Line

### Batteries & Runtime

<b>Run Time</b>	<a href="#">View Runtime Graph</a>
<b>Efficiency</b>	<a href="#">View Efficiency Graph</a>
<b>Battery type</b>	Lead-acid battery
<b>Battery voltage</b>	72 V
<b>Number of battery filled slots</b>	0
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	4 h
<b>Battery life</b>	3...5 year(s)

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Replacement battery	<a href="#">APCRBCV205</a> 
Battery charger power	60 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black (RAL 7010)
Height	33.6 cm
Width	19 cm
Depth	42.5 cm
Net weight	26.8 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
USB compatible	Yes
Mounting position	Vertical

## Input

Input voltage limits	110...285 V half load 160...280 V full load
Network frequency	40...70 Hz auto sensing

## Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Harmonic distortion	3 %
UPS type	Double conversion online
Wave type	Sine wave
Efficiency	88 % (full load)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Bypass type	Internal bypass (automatic and manual)
Crest factor	3 : 1

## Conformance

Product certifications	CE UKCA EAC TISI
------------------------	---------------------------

<b>Standards</b>	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
------------------	--

## Environmental

<b>Ambient air temperature for operation</b>	0...40 °C
<b>Relative humidity</b>	0...95 % non-condensing
<b>Operating altitude</b>	0...3000 m
<b>Ambient air temperature for storage</b>	-20...50 °C
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Storage altitude</b>	0...15000 m
<b>Acoustic level</b>	50 dBA
<b>Heat dissipation</b>	910 Btu/h
<b>IP degree of protection</b>	IP20

## Communications & Management

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
<b>Free slots</b>	1
<b>control panel</b>	Multifunction LCD status and control console

## Surge Protection and Filtering

<b>Surge energy rate</b>	600 J
--------------------------	-------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	46.5 cm
<b>Package 1 Width</b>	32.5 cm
<b>Package 1 Length</b>	56.5 cm
<b>Package 1 Weight</b>	29 kg

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

# Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[How this information helps you >](#)

## Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard **No**

Packaging without single use plastic **No**

[EU RoHS Directive](#) **Compliant**

SCIP Number **080b8d64-796e-42e7-a17d-31b86e55d143**

REACH Regulation [REACH Declaration](#)

### Energy efficiency

Optimized Energy Efficiency **Energy efficient product**

## Use Again

### Repack and remanufacture

[Circularity Profile](#) [End of Life Information](#)

Removable battery **User replaceable**

Take-back

No

---

Image of product / Alternate images

Alternative

---

